


PROJECT:	PREPARED BY:	
PART #	QTY:	
NOTES:	DATE:	








PROJECT:	PREPARED BY:	
PART #	QTY:	
NOTES:	DATE:	







PROJECT:	PREPARED BY:	
PART #	QTY:	
NOTES:	DATE:	








PROJECT:	PREPARED BY:	
PART #	QTY:	
NOTES:	DATE:	







PROJECT	:	PREPARED BY:	
PART	¥	QTY:	
NOTES	:	DATE:	







PROJECT:	PREPARED BY:	
PART #	QTY:	
NOTES:	DATE:	



Unique Coaxial 3-Wheel Design



Easy one-person transport on any terrain.



Special slots are compatible with small warning lights.



A handle that provides the best grip doubles as lift point.




Climbs heights without a forklift if necessary.



Stays stable on muddy ground with maximum contact surface.

Wading depth up to 10cm refers to the water line mark on the light tower body.









PROJECT:	PREPARED BY:	
PART #	QTY:	
NOTES:	DATE:	







PROJECT:	PREPARED BY:	
PART#	QTY:	
NOTES:	DATE:	



Ultra-Long Working Hours



D24-500 (3Kg)

Portable lithium battery with large capacity in a small size



With 3 of fully charged battery power alone, it can provide 10-100 hours lighting.



X3

It also supports using an AC driver for direct power connection.









PROJECT:	PREPARED BY:	
PART #	QTY:	
NOTES:	DATE:	





4.2MBattery-powered
Up To 33,000LM

Battery-powered Up To 35,000 LM

4 Levels of Brightness (Battery Powered)

	Eco	Balanced	Standard	Turbo
5.3M	3,000ьм	10,000гм	18,000гм	35,000гм
4.2M	2,800 LM	9,500гм	17,000гм	33,000 LM

The brightness and battery level can be viewed on the controller when using batteries.



4.2M AC Powered Up To 62,000LM AC Powered Up To 65,000 LM

Stepless Dimmable (AC Powered)







PROJECT:	PREPARED BY:	
PART #	QTY:	
NOTES:	DATE:	








PROJECT:	PREPARED BY:	
PART #	QTY:	
NOTES:	DATE:	







PROJECT:	PREPARED BY:	
PART #	QTY:	
NOTES:	DATE:	



Parameter

TL-500 4.2m

Height	4.2m
Weight	50Kg (Fitting only)
Power Supply	Battery / AC 100-277V
Lumens	Battery 0-33,000LM / AC 0-62,000LM
Run Times	>20h (Standard mode, D24-500 x 3)
IP Grade	IP65
Output(USB)	Type-A (5V 2A) & Type-C (5V 2A)
Battery System	D24 Series

TL-500 5.3m

Height	5.3m
Weight	52Kg (Fitting only)
Power Supply	Battery / AC 100-277V
Lumens	Battery 0-35,000LM / AC 0-65,000LM
Run Times	>20h (Standard mode, D24-500 x 3)
IP Grade	IP65
Output(USB)	Type-A (5V 2A) & Type-C (5V 2A)
Battery System	n D24 Series

Size (cm)

Package

