

PROJECT:	PREPARED BY:	
PART #	QTY:	
NOTES:	DATE:	



# **LLC BREXIT Series POST TOP LIGHT**

A classic antique style Acorn light. Featuring an E39 screw base for lamps. Used for Cities, Towns, Municipalities, Bridges, Parks, Shopping areas, Streets, Schools, Colleges and Universities. Designed and assembled in TN USA.





### **Features**

- Die Cast Aluminum Housing (8 or 9") Clear Lexalite 425
   Series Type III or V Prismatic Globe
- Clear Textured Polycarbonate Top
- Dark Sky Friendly with Internal LiteLid Reflector
- Optional Extras Available (Litelid Reflector/Spike Finial/Clamp Band/Neck Ring)
- Fits Standard 3" O/D Poles
- UL listed Wet Location
- Universal Voltage 120/277V 50/60Hz
- Dims/Weight: 15.9" Dia x 43" High / 24lbs (10.9kg)
- E39 Base for Screw in Lamps (Additional)
- UL certified Wet Location
- Warranty: Limited 10 Year
- Buy American Act Compliant



#### THE LINDY STREET

YOU CAN SEE THAT THE LINDY PROVIDES:

- MORE EFFICIENT LIGHT DISTRIBUTION AND UNIFORMITY TO ILLUMINATE SIDEWALKS AND STREETS
- REDUCED LIGHT WITH DARK SKY FRIENDLY LITELIDS
- MORE EFFICIENT ENERGY USAGE -LOWER WATTAGE LAMPS CAN BE USED
- YEARS OF SUPERIOR PERFORMANCE AND APPEARANCE

DESCRIPTION		
BREXIT SERIES ANTIQUE ACORN LIGHT, 43" TALL, 16" DIA, 3" POST, PRISMATIC TYPE 3 - CLEAR, BLACK FINISH		
BREXIT SERIES ANTIQUE ACORN LIGHT, 43" TALL, 16" DIA, 3" POST, PRISMATIC TYPE 5 - CLEAR, BLACK FINISH		
BREXIT SERIES ANTIQUE ACORN LIGHT, 43" TALL, 16" DIA, 3" POST, PRISMATIC TYPE 3 - CLEAR, WHITE FINISH		
BREXIT SERIES ANTIQUE ACORN LIGHT, 43" TALL, 16" DIA, 3" POST, PRISMATIC TYPE 5 - CLEAR, WHITE FINISH		
BREXIT SERIES ANTIQUE ACORN LIGHT, 43" TALL, 16" DIA, 3" POST, PRISMATIC TYPE 3 - CLEAR, BRONZE FINISH		
BREXIT SERIES ANTIQUE ACORN LIGHT, 43" TALL, 16" DIA, 3" POST, PRISMATIC TYPE 5 - CLEAR, BRONZE FINISH		
LITELID - INTERNAL REFLECTOR - DARK SKY COMPLIANT		
ALUMINUM NECK RING		
SPIKE FINIAL		
ALUMINUM CLAMP BAND		






PROJECT:	PREPARED BY:	
PART#	QTY:	
NOTES:	DATE:	




# **LLC BREXIT Series POST TOP LIGHT**







Report Number: ITL48610
Total Luminaire Efficiency = 81.25%
IES Classification: Type III, Medium, Non-Cutoff



Report Number: ITL48623 Total Luminaire Efficiency = 81.72% IES Classification: Type V, Semi-cutoff

### **Photometrics:**

The Model 424 Type III, coupled with the perforated LiteLid, Model 424 top and a 150W diffuse HPS lamp, produces 7792 candela at 67.5° vertical and 73.3° lateral (ITL48610). The Model 424 Type V, coupled with the perforated LiteLid, Model 424 top and a 150W diffuse HPS lamp, produces 3337 candela at 70° vertical (ITL48623). Both the Type III and V distributions are optimized with diffuse HPS and coated MH lamps. Use of clear lamps may produce reduced uniformity. Individual luminaire performance depends on the lamp center position and the reflector design chosen. Each luminaire design should be individually tested for proper classification. Please call for additional photometric data. Light center location for the Type V shown in report ITL 48623 is 2.7" down from upper rim.





