

PROJECT:		PREPARED BY:	
PART #		QTY:	
NOTES:		DATE:	



Frame Series

Features:

- Novel design, beautiful lighting effect;
- High quality material for good reliability;
- Can be grouped to different patterns to match the architecture style;
- Different dimming modes for option: 0-10V, Dali, Triac, RGBW
- Emergency for option;
- Long lifetime and energy efficient.


Application:

Supermarket, hotel, home, office, restaurant, public building, etc.






Frame Series



CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/3500/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 70
 LED type: Samsung
 Beam angle: 160°
 Installation: Suspended
 Material: Alu+PMMA




Model	Power	Input voltage(V)	Size(mm) L*W*H	Size(Inch) L*W*H
LL0209S-25W	25W	AC220-240V OR AC120-277V 50/60Hz	200*400*70	7.9*15.7*2.8
LL0209S-40W	40W		300*600*70	11.8*23.6*2.8
LL0209S-50W	50W	AC120-277V 50/60Hz	400*800*70	15.7*31.5*2.8
LL0209S-80W	80W		600*1000*70	23.6*39.4*2.8



Up and Down


CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/3500/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 70
 LED type: Samsung
 Beam angle: 280°
 Installation: Suspended
 Material: Alu+PMMA



Model	Power	Input voltage(V)	Size(mm) L*W*H	Size(Inch) L*W*H
LL0210UDS-50W	50W	AC220-240V OR AC120-277V 50/60Hz	200*400*72	7.9*15.7*2.8
LL0210UDS-80W	80W		300*600*72	11.8*23.6*2.8
LL0210UDS-100W	100W	AC120-277V 50/60Hz	400*800*72	15.7*31.5*2.8
LL0210UDS-160W	160W		600*1000*72	23.6*39.4*2.8




CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 105
 LED type: Samsung
 Beam angle: 120°
 Input voltage(V): AC220-240V OR AC120-277V 50/60Hz
 Installation: Suspended / Surface Mounted
 Material: Alu+PC



Model	Power	Suspended		Surface Mounted	
		Size(mm) L*W*H	Size(Inch) L*W*H	Size(mm) L*W*H	Size(Inch) L*W*H
LL01885/M-25W	25W	416*360*85	16.4*14.2*3.4	416*360*75(OD480)	16.4*14.2*3.0
LL01885/M-40W	40W	520*450*85	20.5*17.7*3.4	520*450*75(OD600)	20.5*17.7*3.0
LL01885/M-90W	90W	780*675*85	30.7*26.6*3.4	780*675*75(OD900)	30.7*26.6*3.0
LL01885/M-180W	180W	1039*900*85	40.9*35.4*3.4	1039*900*75(OD1200)	40.9*35.4*3.0



CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 105
 LED type: Samsung
 Beam angle: 120°
 Input voltage(V): AC220-240V or AC120-277V 50/60Hz
 Installation: Suspended / Surface Mounted
 Material: Alu+PC



Model	Power	Suspended		Surface Mounted	
		Size(mm) L*W*H	Size(Inch) L*W*H	Size(mm) L*W*H	Size(Inch) L*W*H
LL01165/M-15W	15W	300*300*75	11.8*11.8*3.0	300*300*85	11.8*11.8*3.4
LL01165/M-40W	40W	600*600*75	23.6*23.6*3.0	600*600*85	23.6*23.6*3.4
LL01165/M-80W	80W	600*1200*75	23.6*47.2*3.0	600*1200*85	23.6*47.2*3.4
LL01165/M-160W	160W	1200*1200*75	47.2*47.2*3.0	1200*1200*85	47.2*47.2*3.4
LL01165/M-320W	320W	1200*2400*75	47.2*94.5*3.0	1200*2400*85	47.2*94.5*3.4






Frame Series




CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 105
 LED type: Samsung
 Beam angle: 160°
 Installation: Suspended
 Material: Alu+PC



Model	Power	Input voltage(V)	Size(mm) L*W*H	Size(Inch) L*W*H
LL01955-40W-U	40W	AC220-240V or AC120-277V 50/60Hz	600*600*25	23.6*23.6*0.98
LL01955-60W-U	60W		900*900*25	35.4*35.4*0.98
LL01955-80W-U	80W		1200*1200*25	47.2*47.2*0.98



CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 105
 LED type: Samsung
 Beam angle: 160°
 Installation: Suspended
 Material: Alu+PC




Model	Power	Input voltage(V)	Size(mm) L*W*H	Size(Inch) L*W*H
LL01955-40W-D	40W	AC220-240V or AC120-277V 50/60Hz	600*600*25	23.6*23.6*0.98
LL01955-60W-D	60W		900*900*25	35.4*35.4*0.98
LL01955-80W-D	80W		1200*1200*25	47.2*47.2*0.98






CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 105
 LED type: Samsung
 Beam angle: 160°
 Installation: Suspended
 Material: Alu+PC



Model	Power	Input voltage(V)	Size(mm) L*W*H	Size(Inch) L*W*H
LL01955-40W-H	40W	AC220-240V	600*600*25	23.6*23.6*0.98
LL01955-60W-H	60W	or AC120-277V	900*900*25	35.4*35.4*0.98
LL01955-80W-H	80W	50/60Hz	1200*1200*25	47.2*47.2*0.98



CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 105
 LED type: Samsung
 Beam angle: 160°
 Installation: Suspended
 Material: Alu+PC




Model	Power	Input voltage(V)	Size(mm) L*W*H	Size(Inch) L*W*H
LL01955-40W-O	40W	AC220-240V	600*600*25	23.6*23.6*0.98
LL01955-60W-O	60W	or AC120-277V	900*900*25	35.4*35.4*0.98
LL01955-80W-O	80W	50/60Hz	1200*1200*25	47.2*47.2*0.98






CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 105
 LED type: Samsung
 Beam angle: 120°
 Installation: Surface Mounted
 Material: Alu+PC



Model	Power	Input voltage(V)	Size(mm) L*W*H	Size(Inch) L*W*H
LL0187M-25W	25W	AC220-240V or AC120-277V 50/60Hz	480*416*85(ID480)	18.9*16.4*3.4
LL0187M-40W	40W		600*520*85(ID600)	23.6*20.5*3.4
LL0187M-90W	90W	AC120-277V 50/60Hz	900*780*85(ID900)	35.4*30.7*3.4
LL0187M-180W	180W		1200*1040*85(ID1200)	47.2*40.9*3.4



CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 105
 LED type: Samsung
 Beam angle: 120°
 Installation: Suspended
 Material: Alu+PC



Model	Power	Input voltage(V)	Size(mm) L*W*H	Size(Inch) L*W*H
LL0187S-25W	25W	AC220-240V or AC120-277V 50/60Hz	480*416*75(ID480)	18.9*16.4*3.0
LL0187S-40W	40W		600*520*75(ID600)	23.6*20.5*3.0
LL0187S-90W	90W	AC120-277V 50/60Hz	900*780*75(ID900)	35.4*30.7*3.0
LL0187S-180W	180W		1200*1040*75(ID1200)	47.2*40.9*3.0

PROJECT:		PREPARED BY:	
PART #		QTY:	
NOTES:		DATE:	




- Features:**
- Novel design, beautiful lighting effect;
 - High quality material for good reliability;
 - Can be grouped to different patterns to match the architecture style;
 - Different dimming modes for option: 0-10V, Dali, Triac, RGBW
 - Emergency for option;
 - Long lifetime and energy efficient.
- Application:**
Supermarket, hotel, home, office, restaurant, public building, etc.

Frame Series



CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: > 0.9
 Efficiency(LM/W): 105
 LED type: Samsung
 Beam angle: 120°
 Installation: Suspended
 Material: Alu+PC



Model	Power	Input voltage(V)	Size(mm) L*W*H	Size(Inch) L*W*H
LL01905/M-40W	40W	AC220-240V	563*501*75(L300)	22.2*19.7*3.0/3.4
LL01905/M-80W	80W	or AC220-277V	1081*963*75(L600)	42.6*37.9*3.0/3.4
LL01905/M-120W	120W	50/60Hz	1600*1426*75(L900)	63.0*56.1*3.0/3.4

