


PROJECT:		PREPARED BY:	
PART #:		QTY:	
NOTES:		DATE:	



Ring Series

Technical specifications and diagrams for the Ring Series light fixture:




- Dimensions: 68(2.7) inches height, 42(1.7) inches diameter.
- Light Distribution Curve: Average beam angle 55°, 2°/120°.
- Color options: SATIN WHITE (SW), SATIN BLACK (SB), RAL.
- OSRAM and SAMSUNG LED technology.
- Features: Architectural, Indoor, Protective grounding, High efficiency, No flicker, Remote location, Dimmable, DALI, 5 Year Warranty, Color tuning, RGB.

Model	Input Voltage(V)	Power	CRI	CCT (K)	PF	Efficacy (l M/W)	LED	Beam (degree)	Installation	Material	Size(mm) D*W*H	Size(Inch) D*W*H
LL0115UDS-80W	AC220-240V or AC120-277V 50/60Hz	80W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	85	Samsung	120*2	Suspended	Alu+PC	D900*42*68	D35.4*1.7*2.7
LL0115UDS-120W		120W									D1200*42*68	D47.2*1.7*2.7
LL0115UDS-135W		135W									D1500*42*68	D59.1*1.7*2.7
LL0115UDS-150W		150W									D2000*42*68	D78.7*1.7*2.7
LL0115UDS-300W		300W									D3000*42*68	D118.1*1.7*2.7
LL0115UDS-480W		480W									D5000*42*68	D196.9*1.7*2.7





Ring Series



Model	Input Voltage(V)	Power	CRI	CCT (K)	PF	Efficacy (LM/W)	LED	Beam (degree)	Installation	Material	Size(mm) D*W*H	Size(Inch) D*W*H
LL0113S/M-40W	AC220-240V or AC120-277V 50/60Hz	40W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	85	Samsung	120	Suspended / Mounted	Alu+PC	D600*32*38	D23.6*1.3*1.5
LL0113S/M-50W		50W									D900*32*38	D35.4*1.3*1.5
LL0113S/M-80W		80W									D1200*32*38	D47.2*1.3*1.5
LL0113S/M-100W		100W									D1500*32*38	D59.1*1.3*1.5
LL0113S/M-120W		120W									D2000*32*38	D78.8*1.3*1.5
LL0113S/M-200W		200W									L3000*32*38	D118.1*1.3*1.5
LL0113S/M-400W		400W									D5000*32*38	D196.9*1.3*1.5

PROJECT:		PREPARED BY:	
PART #		QTY:	
NOTES:		DATE:	

Ring Series









Model	Input Voltage(V)	Power	CRI	CCT (K)	PF	Efficacy (LM/W)	LED	Beam (degree)	Installation	Material	Size(mm) D*W*H	Size(Inch) D*W*H
LL0125S-32W	AC220-240V or AC120-277V 50/60Hz	32W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	70lm/w	Samsung	300	Suspended	Alu+PC	D600*35*32	D23.6*1.4*1.3
LL0125S-40W		40W									D900*35*32	D35.4*1.4*1.3
LL0125S-70W		70W									D1200*35*32	D47.2*1.4*1.3
LL0125S-80W		80W									D1500*35*32	D59.1*1.4*1.3
LL0125M-32W	AC220-240V or AC120-277V 50/60Hz	32W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	70lm/w	Samsung	300	Mounted	Alu+PC	D600*35*32	D23.6*1.4*1.3
LL0125M-40W		40W									D900*35*32	D35.4*1.4*1.3
LL0125M-70W		70W									D1200*35*32	D47.2*1.4*1.3
LL0125M-80W		80W									D1500*35*32	D59.1*1.4*1.3
LL0126S-32W	AC220-240V or AC120-277V 50/60Hz	32W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	70lm/w	Samsung	300	Suspended	Alu+PC	D600*35*32	D23.6*1.4*1.3
LL0126S-40W		40W									D900*35*32	D35.4*1.4*1.3
LL0126S-70W		70W									D1200*35*32	D47.2*1.4*1.3
LL0126S-80W		80W									D1500*35*32	D59.1*1.4*1.3
LL0126M-32W	AC220-240V or AC120-277V 50/60Hz	32W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	70lm/w	Samsung	300	Mounted	Alu+PC	D600*35*32	D23.6*1.4*1.3
LL0126M-40W		40W									D900*35*32	D35.4*1.4*1.3
LL0126M-70W		70W									D1200*35*32	D47.2*1.4*1.3
LL0126M-80W		80W									D1500*35*32	D59.1*1.4*1.3



PROJECT:		PREPARED BY:	
PART #		QTY:	
NOTES:		DATE:	



Ring Lighting Series





PROJECT:		PREPARED BY:	
PART #		QTY:	
NOTES:		DATE:	


Ring Lighting Series





CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 70
 LED type: Samsung
 Beam angle: 160°
 Installation: Suspended
 Material: Alu+PMMA



Model	Power	Input voltage(V)	Size(mm) D*W*H	Size(Inch) D*W*H
LL02035-15W	15W	AC220-240V or AC120-277V 50/60Hz	D400*13*70	D15.7*0.5*2.8
LL02035-25W	25W		D600*13*70	D23.6*0.5*2.8
LL02035-35W	35W		D800*13*70	D31.5*0.5*2.8
LL02035-45W	45W		D1000*13*70	D39.4*0.5*2.8
LL02035-50W	50W		D1200*13*70	D47.2*0.5*2.8
LL02035-60W	60W		D1500*13*70	D59.1*0.5*2.8



CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 70
 LED type: Samsung
 Beam angle: 280°
 Installation: Suspended
 Material: Alu+PMMA



Model	Power	Input voltage(V)	Size(mm) D*W*H	Size(Inch) D*W*H
LL0204UDS-30W	30W	AC220-240V or AC120-277V 50/60Hz	D400*13*72	D15.7*0.5*2.8
LL0204UDS-50W	50W		D600*13*72	D23.6*0.5*2.8
LL0204UDS-60W	60W		D800*13*72	D31.5*0.5*2.8
LL0204UDS-80W	80W		D1000*13*72	D39.4*0.5*2.8
LL0204UDS-90W	90W		D1200*13*72	D47.2*0.5*2.8
LL0204UDS-100W	100W		D1500*13*72	D59.1*0.5*2.8



PROJECT:		PREPARED BY:	
PART #		QTY:	
NOTES:		DATE:	

Ring Series




PROJECT:		PREPARED BY:	
PART #		QTY:	
NOTES:		DATE:	

Ring Series




CR(Ra): ≥80 or ≥90
 CCT(K): 3000/4000/5000
 PF: ≥0.9
 Efficiency(LM/W): 70
 LED type: Samsung
 Beam angle: 300°
 Installation: Suspended
 Material: Alu+PC



Model	Power	Input voltage(V)	Size(mm) D*W*H	Size(Inch) D*W*H
LL02075-20W	20W	AC220-240V or AC120-277V 50/60Hz	D400*10*20	D15.7*0.4*0.8
LL02075-30W	30W		D600*10*20	D23.6*0.4*0.8
LL02075-40W	40W		D800*10*20	D31.5*0.4*0.8
LL02075-50W	50W		D1000*10*20	D39.4*0.4*0.8
LL02075-60W	60W		D1200*10*20	D47.2*0.4*0.8
LL02075-80W	80W		D1500*10*20	D59.1*0.4*0.8



CR(Ra): ≥80 or ≥90
 CCT(K): 3000/4000/5000
 PF: ≥0.9
 Efficiency(LM/W): 70
 LED type: Samsung
 Beam angle: 300°
 Installation: Suspended
 Material: Alu+PC




Model	Power	Input voltage(V)	Size(mm) D*W*H	Size(Inch) D*W*H
LL02085-20W	20W	AC220-240V or AC120-277V 50/60Hz	D400*10*20	D15.7*0.4*0.8
LL02085-30W	30W		D600*10*20	D23.6*0.4*0.8
LL02085-40W	40W		D800*10*20	D31.5*0.4*0.8
LL02085-50W	50W		D1000*10*20	D39.4*0.4*0.8
LL02085-60W	60W		D1200*10*20	D47.2*0.4*0.8
LL02085-80W	80W		D1500*10*20	D59.1*0.4*0.8






CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 70
 LED type: Samsung
 Beam angle: 360°
 Installation: Suspended with 1.5m power cable and safety cable
 Material: PE
 Body color: White



Model	Power	Input voltage(V)	Size(mm) D*H	Size(Inch) D*H
LL0175S-25W	25W	AC220-240V OR AC120-277V 50/60Hz	D400*60	D15.7*2.6
LL0175S-36W	36W		D600*60	D23.6*2.6
LL0175S-60W	60W		D900*60	D35.4*2.6
LL0175S-80W	80W		D1200*60	D47.2*2.6
LL0175S-100W	100W		D1500*60	D59.0*2.6
LL0175S-120W	120W		D1800*60	D70.8*2.6



CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 70
 LED type: Samsung
 Beam angle: 360°
 Installation: Surface mounted
 Material: PE
 Body color: White



Model	Power	Input voltage(V)	Size(mm) D*H	Size(Inch) D*H
LL0175M-25W	25W	AC220-240V OR AC120-277V 50/60Hz	D400*95	D15.7*3.7
LL0175M-36W	36W		D600*95	D23.6*3.7
LL0175M-60W	60W		D900*95	D35.4*3.7
LL0175M-80W	80W		D1200*95	D47.2*3.7
LL0175M-100W	100W		D1500*95	D59.0*3.7
LL0175M-120W	120W		D1800*95	D70.8*3.7